

Accurate testing is easy with the new Pooltest 9 Professional.



Pooltest 9 Professional

The Pooltest 9 has become the world's best-selling pool photometer, thanks to its reliability and ease of use. The new Pooltest 9 Professional builds on the phenomenal success of its predecessor, offering even more great features:

- Fully Waterproof with IP67 rating: It even floats
- Large backlit screen
- Unique adaptive sample holder
- Automatic wavelength and method selection

The Pooltest 9 Professional is fast and easy to use. The results are displayed in mg/l or ppm. It measures all the routine pool parameters, all disinfectants, balanced water tests and is fully integrated with the world renowned Palintest tablet test reagents.

SP 790 Pooltest 9 Professional Kit

The kit comes complete with 20 tests each for Free and Total Chlorine, Ozone, pH (Phenol Red) and Copper, plus 10 tests each for Alkalinity, Calcium Hardness and Cyanuric Acid. The kit includes 4 photometer test tubes and is supplied in a hard plastic carry case.



PT 804 Check Standards

PT 265 Alkaline Batteries

Reagents

TEST	RANGE (mg/l)	REAGENT PACKS (50 TESTS)	REAGENT PACKS (250 TESTS)
Alkalinity Total (Alkaphot)	0-500 (CaCO ₃)	PM 188	AP 188
Cyanuric Acid	0-200	PM 087	AP 087
Bromine	0-10.0	PM 060	AP 060
Calcium Hardness (Calcicol)	0-500 (CaCO ₃)	PM 252	AP 252
Chlorine DPD 1	0-5.0	PM 011	AP 011
Chlorine DPD 1 & 3	0-5.0	PM 031	AP 031
Copper (Coppercol) (free, combined, and total)	0-5.0	PM 186	AP 186
Ozone	0-2.0	PM 056	AP 056
pH (phenol red)	6.8-8.4	PM 130	AP 130

Technical Specifications

Instrument Type	Direct-reading colorimeter with automatic set-up and reading
Pre-programmed Tests	Free Chlorine, Total Chlorine, pH, Cyanuric Acid, Alkalinity, Ozone, Calcium Hardness, Copper and Bromine
Operating Wavelengths	450 nm, 500 nm, 550 nm, 575 nm, 600 nm and 650 nm
Display	Large Backlit graphic LCD screen
Accuracy	± 0.005 at 0.3 AU
Resolution	0.001 AU
User Selectable Options	Display language Test units
Test Cells	Automatic adjustment for round test tubes from 12 - 20 mm diameter
Power	Battery power (3 x 'AA')
Size	W146 x D275 x H75 mm
Weight	975g
Instrument Rating	Waterproof IP67

Palintest Ltd

Palintest House, Kingsway, Team Valley, Gateshead, Tyne & Wear, NE11 0NS, England
Tel: +44 (0) 191 491 0808
Fax: +44 (0) 191 482 5372
Email: sales@palintest.com
Website: www.palintest.com

Palintest USA

21 Kenton Lands Road, Erlanger, Kentucky 41018, USA
Tel: (859) 341 7423 **Toll Free:** 800 835 9629
Fax: (859) 341 2106
Email: info@palintestusa.com
Website: www.palintestusa.com

Palintest Australia

21/53 Lorraine Street, Peakhurst Business Centre, Peakhurst NSW 2210, Australia
Tel: 1300 131516
Fax: 1300 131986
Email: palintest@palintest.com.au
Website: www.palintest.com.au